


Updated: February 2011

PLUG LID CANS ■

- Article:** Plug lid cans out of tinplate
- Sealing:**
- welded side seam
 - bottom sealed
 - lid with or without rubber sealing
- Body form:**
- cylindrical
- Closures:**
- CL = lid securing clip
 - CR = clamping ring
 - SPM = strip sealing system
 - L-Ring



Plug lid cans are tried and tested tinplate containers that have a variety of uses. The can body is equipped with an external curl and the lid is inserted directly.

Nominal capacity liter	Ø mm	Height mm	Closures				Design type approval		
			CL	CR	SPM	L-Ring	without	RID/ADR	UN
0,25	73	74	■				■		
0,50	99	79	■	■	■	■	■		
0,50	99	79			■				UN/1A2/Y/100
0,50	163/155	70		■	■	■			UN/1A2/Y/100
0,75	99	116	■	■	■	■	■		
0,75	99	116			■				UN/1A2/Y/100
1,0	99	151	■	■	■	■	■		
1,0	99	151			■				UN/1A2/Y/100
1,0	116	130	■				■		
1,0	163	90	■	■	■	■	■		
1,0	163/155	90		■	■	■			UN/1A2/Y/100
1,5	163	110		■				RID/ADR/0A2/Y5/S	
2,5	163	144		■				RID/ADR/0A2/Y5/S	
2,5	163	145	■	■	■		■		
3,5	163/155	180		■	■			RID/ADR/0A2/Y6/S	UN/1A2/Y/100
3,5	163	181		■				RID/ADR/0A2/Y5/S	
3,5	163	182	■	■	■		■		
4	163	212		■				RID/ADR/0A2/Y/100	
4	163	213	■	■	■		■		