

We live packaging.




Stand: Januar 2009

TWIN PACK. ■

Two-component-packaging system Twin Pack Stack-on system

Component A (bottom):

- Article:** Hobcock out of tinplate
- Sealing:**
- welded side seam
 - bottom sealed
 - lid with rubber sealing
- Carrying device:** ■ two side drop handle
- Body form:** ■ conical
- Closure:** ■ ACR = asymmetrical clamping ring
is simultaneously used for joining A- and B- container



Component B (top):

- Article:** Plug lid can out of tinplate
- Sealing:**
- welded side seam
 - bottom sealed
 - lid with rubber sealing
- Body form:** ■ conical
- Closure:** ■ CR = clamping ring – regular shape

- Joining A / B** ■ asymmetrical clamping ring of component A

The TwinPack range offers the ideal packaging for the filling, storage, transport and application of two-component products. Each of the two units is filled separately and then connected to a storage and transportation unit by placing the B-container on top of the A-container. The asymmetrical clamping ring serves both as a closure for component A and also as a joining element. By incorporating the necessary space at the top of container A, component B can be mixed in correctly when using the contents.

We live packaging.



Stand: Januar 2009

TwinPack - stack-on system

Nominal capacity liter	Ø mm	Height mm	Closures			Design type approval		
			ACR	CR	SPM	without	RID/ADR	UN
Component A (bottom)								
12	280/262	225	■				RID/ADR/0A2/Y37/S	UN/1A2/Y/100
15	280/262	295	■				RID/ADR/0A2/Y37/S	
20	280/262	376	■				RID/ADR/0A2/Y37/S	UN/1A2/Y/100
20	280/262	391	■				RID/ADR/0A2/Y37/S	UN/1A2/Y/100
20	280/262	400	■				RID/ADR/0A2/Y37/S	
25	328/312	284	■				RID/ADR/0A2/Y41/S	UN/1A2/Y/100
25	328/312	353	■				RID/ADR/0A2/Y41/S	UN/1A2/Y/100
27	328/312	370	■				RID/ADR/0A2/Y41/S	UN/1A2/Y/100
29	328/312	390	■				RID/ADR/0A2/Y41/S	UN/1A2/Y/100
29	328/312	410	■				RID/ADR/0A2/Y41/S	UN/1A2/Y/100
31	328/312	425	■				RID/ADR/0A2/Y41/S	UN/1A2/Y/100
Component B (top)								
4	280/262	100		■				UN/1A2/Y/100
7	280/262	150		■				UN/1A2/Y/100
6	328/312	100		■			RID/ADR/0A2/Y/100	
10	328/312	150		■			RID/ADR/0A2/Y/100	

