

We live packaging.

**HUBER**  
PACKAGING GROUP


Updated: January 2009

## TWIN PACK. ■

### Two-component-packaging system Twin Pack Suspended system with snap-on lid

#### Component A (top):

- Article:** Plug lid pail out of tinplate
- Sealing:**
- welded side seam
  - bottom sealed
  - lid with rubber sealing
- Carrying device:**
- wire bail with ball ears
- Body form:**
- 1) cylindrical
  - 2) drawn in at bottom
- Closures:**
- CR = clamping ring
  - SPM = strip sealing system
  - L-Ring



#### Component B (bottom):

- Article:** Plug lid can out of tinplate
- Sealing:**
- welded side seam
  - bottom sealed
  - lid with rubber sealing
- Body form:**
- 1) cylindrical
  - 2) drawn in at bottom
- Closure:**
- SPM = strip sealing system
  - L-Ring
  - with opening for plastic closure with flexible pouring spout 57 mm

- Joining A / B**
- snap-on lid on B-component

The TwinPack range offers the ideal packaging for the filling, storage, transport and application of two-component products. Each of the two units is filled separately and then connected to a storage and transportation unit. To join the two packaging components the bottom seam of the A-container is locked in the lid of the B-component. There is no need for any further connecting element. By incorporating the necessary space at the top of container A, component B can be mixed in correctly when using the contents.

We live packaging.



Updated: January 2009

## TwinPack - suspended system

Nominal capacity liter	Ø mm	Height mm	Closure			Design type approval		
			CR	SPM	L-Ring	without	RID/ADR	UN
<b>Component A (top)</b>								
3	163/156 <sup>2)</sup>	180	■	■				UN/1A2/Y/100
<b>Component B (bottom)</b>								
1	163/156 <sup>1)2)</sup>	70			■			UN/1A2/Y/100
1,25	163/156 <sup>1)2)</sup>	90			■			UN/1A2/Y/100
<b>Component A (top)</b>								
6	230/217	175	■	■			RID/ADR/0A2/Y17/S	
6	230/217	175	■	■	■			UN/1A2/Y/100
10	230/217	227	■	■			RID/ADR/0A2/Y17/S	
10	230/217	227	■	■	■			UN/1A2/Y/100
10	230/217	281	■	■			RID/ADR/0A2/Y17/S	
10	230/217	281	■	■	■			UN/1A2/Y/100
12	230/217	300	■	■			RID/ADR/0A2/Y17/S	
12	230/217	300	■	■	■			UN/1A2/Y/100
12	230/217	325	■	■			RID/ADR/0A2/Y17/S	
12	230/217	325	■	■	■			UN/1A2/Y/100
12	230/217	340	■	■			RID/ADR/0A2/Y17/S	
12	230/217	340	■	■	■			UN/1A2/Y/100
<b>Component B (bottom)</b>								
1,5	223/217	70		■	■			UN/1A2/Y/100
2	223/217	80		■	■			UN/1A2/Y/100
3	223/217	95		■	■			UN/1A2/Y/100
3,5	223/217	110		■	■			UN/1A2/Y/100

